



PIGNONI PER BUSSOLA CONICA TEMPERATI AD INDUZIONE - DIN 8187 - ISO 606

SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH - DIN 8187 - ISO 606

3/8" x 7/32"

9,525 x 5,72 mm
Rullo 6,35 mm
06B - 1





B1	C	r3
5,3	1	10

Materiale C 43 UNI 7847

Z	de	dp	dm	semplici		
				A	bussola	Kg.
17	55,5	51,83	45	22	1008	0,11
19	61,6	57,86	45	22	1008	0,15
21	67,6	63,90	46	22	1008	0,18
23	73,7	69,95	63	25	1210	0,27
25	79,7	75,99	63	25	1210	0,32

1/2" x 5/16"

12,7 x 7,75 mm
Rullo 8,51 mm
08B - 1





B1	C	r3
7,2	1,3	13

Materiale C 43 UNI 7847

Z	de	dp	dm	semplici		
				A	bussola	Kg.
15	66,5	61,80	45	22	1008	0,16
17	74,5	69,11	60	25	1210	0,22
19	82,5	77,15	63	25	1210	0,33
21	90,6	85,21	71	25	1610	0,36
23	98,7	93,26	76	25	1610	0,50

5/8" x 3/8"

15,875 x 9,65 mm
Rullo 10,16 mm
10B - 1



B1	C	r3
9,1	1,6	16

Materiale C 43 UNI 7847

Z	de	dp	dm	semplici		
				A	bussola	Kg.
13	73,2	66,33	47	22	1008	0,23
15	83,2	76,35	60	25	1210	0,30
17	93,3	86,39	71	25	1610	0,38
19	103,3	96,44	75	25	1610	0,54
21	113,4	106,51	76	25	1610	0,65

PIGNONI PER BUSSOLA CONICA TEMPERATI AD INDUZIONE - DIN 8187 - ISO 606




SPROCKETS FOR TAPER BUSHES WITH HARDENED TEETH - DIN 8187 - ISO 606

3/4" x 7/16"

19,05 x 11,68 mm
Rullo 12,07 mm
12B - 1

B1	C	r3
11,1	2	19

Materiale: C 43 UNI 7847



Z	de	dp	dm	semplici		
				A	bussola	Kg.
13	87,8	79,60	60	25	1210	0,35
15	99,8	91,62	70	25	1610	0,44
17	111,9	103,67	76	25	1610	0,66
19	123,9	115,73	90	32	2012	0,94
21	136,0	127,81	102	44	2517	1,24



Z	de	dp	dm	semplici		
				A	bussola	Kg.
23	148,1	139,90	108	44	2517	1,70
25	160,2	151,99	108	44	2517	1,93
27	172,3	164,09	108	44	2517	2,14
30	190,4	182,24	108	44	2517	2,60

1" x 17,02 mm

25,4 x 17,02 mm
Rullo 15,88 mm
16B - 1

B1	C	r3
16,2	2,5	26

Materiale: C 43 UNI 7847



Z	de	dp	dm	semplici		
				A	bussola	Kg.
15	133,7	122,16	76	38	1615	1,30
17	149,8	138,23	90	32	2012	1,59
19	165,9	154,31	108	44	2517	2,29
21	182,0	170,42	110	44	2517	2,81
23	198,1	186,53	110	44	2517	3,38



Z	de	dp	dm	semplici		
				A	bussola	Kg.
25	214,2	202,66	110	44	2517	3,97
27	230,4	218,79	110	44	2517	4,55
30	254,6	242,99	120	44	2517	5,97

1"1/4 x 3/4"

31,75 x 19,56 mm
Rullo 19,05 mm
20B - 1

B1	C	r3
18,5	3,5	32

Materiale: C 43 UNI 7847



Z	de	dp	dm	semplici		
				A	bussola	Kg.
15	167,7	152,72	110	44	2517	3,39
17	187,7	172,78	110	44	2517	5,07
19	207,9	192,91	110	44	2517	6,75
21	228,0	213,04	120	44	2517	7,70
23	248,2	233,17	120	44	2517	8,78

Z	de	dp	dm	semplici		
				A	bussola	Kg.
25	268,4	253,33	120	44	2517	9,50